

# DRAWING INDEX

- C100 COVER SHEET / LIFE SAFETY INFORMATION
- C000 CIVIL COVER SHEET
- C001 GENERAL AND SWPPP NOTES
- C100 EXISTING CONDITIONS AND DEMOLITION PLAN
- C200 SITE AND GRADING PLAN
- C820 SITE DETAILS
- A101 PRE-ENGINEERED METAL BUILDING DETAILS
- S-1 FOUNDATION/SLAB PLAN, SECTIONS
- M101 HVAC PLAN
- P101 PLUMBING PLANS
- E0.1 ELECTRICAL SPECIFICATION, RISER DIAGRAM & DETAILS
- E0.2 ELECTRICAL LIGHT FIXTURE SCHEDULE
- E1.1 ELECTRICAL LIGHTING PLAN
- E2.1 ELECTRICAL POWER PLAN

# DRY STORAGE BUILDING

# PIEDMONT TECHNICAL COLLEGE

# Greenwood, SC

**H59-N309-TM**

# BID DOCUMENTS



COPYRIGHT © 2025 CRAIG GAULDEN & DAVIS, INC.  
ALL RIGHTS RESERVED

THIS COPYRIGHTED DOCUMENT AND ALL INFORMATION CONTAINED HEREIN IS AN INSTRUMENT OF SERVICE AND SHALL NOT BE REPRODUCED, ALTERED, OR REUSED IN PART OR IN WHOLE WITHOUT PRIOR WRITTEN PERMISSION FROM THE ARCHITECT. THIS DRAWING IS THE EXCLUSIVE PROPERTY OF THE ARCHITECT AND MUST BE RETURNED UPON REQUEST.

PROJECT

## A NEW DRY STORAGE BUILDING

# PIEDMONT TECHNICAL COLLEGE

OSE # H59-N309-TM  
GREENWOOD, SC

MARK	DATE	DESCRIPTION
------	------	-------------

ISSUE:	BID DOCUMENTS
DATE:	11/25/25
PROJECT NO.:	25010
DRAWN BY:	DLD
CHECKED BY:	DLD

# **COVER SHEET**

# **LIFE SAFETY**


# **PLAN**

C10


# PTC - DRY STORAGE BUILDING

# PIEDMONT TECHNICAL COLLEGE GREENWOOD, SOUTH CAROLINA

<h2>PROJECT SUMMARY</h2>	
<u>PROJECT NAME:</u>	PTC - DRY STORAGE BUILDING
<u>PROJECT ADDRESS:</u>	1924 KATEWAY, GREENWOOD, SOUTH CAROLINA
<u>PROJECT DESCRIPTION:</u>	THE PROPOSED PROJECT WILL INCLUDE A NEW 60' X 100' STORAGE BUILDING AND CONCRETE APRON.
<u>TAX MAP PARCEL INFORMATION:</u>	TMS# 6866-083-513
<u>SITE ACREAGE:</u>	
DISTURBED ACRES:	0.71 AC.







# LOCATION MAP



# VICINITY MAP

SHEET LIST TABLE		
PAGE #	SHEET #	SHEET TITLE
1	C000	COVER
2	C001	GENERAL AND SWPPP NOTES
3	C100	EXISTING CONDITIONS AND DEMOLITION PLAN
4	C200	SITE AND GRADING PLAN
5	C820	SITE DETAILS (SHEET 1 OF 2)



:\\Jobsodd\\14341-00\\Production\\Civil\\Drawings\\014341-00-GENERAL.dwg, 12/2/2025 1:17:55 PM, sean goggins, et  
THESE DRAWINGS AND THE DESIGN THEREON ARE THE PROPERTY OF DAVIS & ELROY INC. AND MAY NOT BE USED IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT OF THE ENGINEER / ARCHITECT AND ANY INFRINGEMENT WILL BE SUBJECT TO LEGAL ACTION

## UNDERGROUND FACILITIES

EXISTING UNDERGROUND FACILITIES AT THE SITE HAVE NOT BEEN INDIVIDUALLY VERIFIED BY THE OWNER OR ITS REPRESENTATIVE AND ARE APPROXIMATE ONLY. EXISTING UNDERGROUND FACILITIES ARE CONSIDERED TO BE ALL ACTIVE OR NOT-IN-SERVICE UNDERGROUND LINES, PIPELINES, CONDUITS, DUCTS, ENCASEMENTS, CABLES, WIRES, MANHOLES, VAULTS, TANKS, TUNNELS, OR OTHER SUCH FACILITIES OR SYSTEMS AT THE SITE, INCLUDING BUT NOT LIMITED TO THOSE FACILITIES OR SYSTEMS THAT PRODUCE, TRANSMIT, DISTRIBUTE, OR CONVEY TELEPHONE OR OTHER COMMUNICATIONS, CABLE TELEVISION, FIBER OPTIC TRANSMISSIONS, POWER, ELECTRICITY, LIGHT, HEAT, GASES, OIL, CRUDE OIL PRODUCTS, LIQUID PETROLEUM PRODUCTS, WATER, STEAM, WASTE, WASTEWATER, STORM WATER, OTHER LIQUIDS OR CHEMICALS, OR TRAFFIC OR OTHER CONTROL SYSTEMS. UNLESS IT IS OTHERWISE EXPRESSLY PROVIDED IN THE SUPPLEMENTARY CONDITIONS OF THE CONSTRUCTION CONTRACT, THE COST OF ALL OF THE FOLLOWING ARE INCLUDED IN THE CONTRACT PRICE, AND CONTRACTOR SHALL HAVE FULL RESPONSIBILITY FOR:


1. REVIEWING AND CHECKING ALL INFORMATION AND DATA REGARDING EXISTING UNDERGROUND FACILITIES AT THE SITE;
2. COMPLYING WITH APPLICABLE STATE AND LOCAL UTILITY DAMAGE PREVENTION LAWS AND REGULATIONS;
3. VERIFYING THE ACTUAL LOCATION OF THOSE UNDERGROUND FACILITIES SHOWN OR INDICATED IN THE CONTRACT DOCUMENTS AS BEING WITHIN THE AREA AFFECTED BY THE WORK, BY EXPOSING SUCH UNDERGROUND FACILITIES DURING THE COURSE OF CONSTRUCTION;
4. COORDINATION OF THE WORK WITH THE FACILITY OWNERS (INCLUDING PROJECT OWNER) OF SUCH UNDERGROUND FACILITIES, DURING CONSTRUCTION;
5. THE SAFETY AND PROTECTION OF ALL EXISTING UNDERGROUND FACILITIES AT THE SITE AND REPAIRING ANY DAMAGE THERETO RESULTING FROM THE WORK; AND
6. ANY AND ALL DAMAGE WHICH OCCURS DUE TO THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE, PROTECT, AND PRESERVE ANY AND ALL UNDERGROUND FACILITIES.

<h2 style="margin: 0;">ENGINEER CERTIFICATIONS</h2>	
<p>         "I HAVE PLACED MY SIGNATURE AND SEAL ON THE DESIGN DOCUMENTS SUBMITTED          SIGNIFYING THAT I ACCEPT RESPONSIBILITY FOR THE DESIGN OF THE SYSTEM.          FURTHER, I CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THAT THE DESIGN IS          CONSISTENT WITH THE REQUIREMENTS OF TITLE 48, CHAPTER 14 OF THE CODE OF LAWS          OF SC, 1976 AS AMENDED, PURSUANT TO REGULATION 72-300 ET SEQ. (IF APPLICABLE),          AND IN ACCORDANCE WITH THE TERMS AND CONDITIONS OF SCR100000."       </p>	
<u>08/25/2025</u>	
DATE	SIGNATURE

<u>DEVELOPER</u>	<u>CIVIL ENGINEER</u>	<u>SURVEYOR</u>
PIEDMONT TECHNICAL COLLEGE 620 EMERALD ROAD NORTH GREENWOOD, SC Z29648 PHONE	DAVIS & FLOYD, INC. JAMES D. COMPTON, P.E. 164 MILESTONE WAY GREENVILLE, SC 29615 (864)527-9800	DAVIS & FLOYD, INC. JEFFREY POOLE P.L.S. 1319 HIGHWAY 72/221 GREENWOOD, SC 29649 (864)229-5211



Know what's below.  
Call before you dig.



## GRADING, AND DRAINAGE

- THE CONTRACTOR SHALL BE RESPONSIBLE FOR MANAGING CONSTRUCTION ACTIVITIES AT ALL TIMES TO ENSURE THAT PUBLIC STREETS AND RIGHT-OF-WAYS ARE KEPT CLEAN OF MUD, DUST, OR DEBRIS. DUST ABATEMENT SHALL BE MAINTAINED BY ADEQUATE WATERING OF THE SITE BY THE CONTRACTOR.
- FOR GRADING, PAVING, AND DRAINAGE WORK LOCATED WITHIN SCDOT AND/OR PUBLIC RIGHTS-OF-WAY, ALL MATERIALS AND EQUIPMENT, UNLESS SPECIFICALLY STATED OTHERWISE HEREIN, SHALL BE IN ACCORDANCE WITH REQUIREMENTS OF THE SCOT STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, LATEST EDITION.
- STRIP WORK LIMITS, REMOVING ALL ORGANIC MATTER WHICH CAN NOT BE COMPACTED INTO A STABLE MASS. ALL TREES, BRUSH AND DEBRIS ASSOCIATED WITH CLEARING, STRIPPING OR GRADING SHALL BE REMOVED AND DISPOSED OF OFF-SITE BY THE CONTRACTOR. ANY TREES MARKED OR SUSPECTED OF BEING PROTECTED SHALL BE COORDINATED THROUGH THE OWNER, ENGINEER, AND THE LOCAL JURISDICTION PRIOR TO REMOVAL.
- UNLESS SPECIFICALLY STATED OTHERWISE, ALL FILL SHALL BE APPROVED BY THE ENGINEER AND BE UNIFORMLY SPREAD IN MAXIMUM 8" THICK LOOSE LIFTS AND SHALL BE COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY PER AASHTO T-180 TEST METHOD (MODIFIED PROCTOR) AND BE WITHIN 3% OF THE OPTIMUM MOISTURE CONTENT. ANY ROCK FRAGMENTS WITHIN THE NEW FILL SHOULD BE LESS THAN 2" IN DIAMETER.
- THE CONTRACTOR SHALL RESTORE ALL AREAS DISTURBED BY CONSTRUCTION TO GRADES THAT RESULT IN POSITIVE DRAINAGE TO THE EXISTING AND/OR NEW STORM DRAINAGE INLETS, UNLESS OTHERWISE NOTED.
- CONTRACTOR SHALL REVIEW THE GEOTECHNICAL REPORT IN FILL. SEE "REPORT OF GEOTECHNICAL EXPLORATION - PIEDMONT TECHNICAL COLLEGE - DRY STORAGE BUILDING" BY GEOTRACK, DATED 04/08/2025.

## SCDES STANDARD NOTES

- IF NECESSARY, SLOPES, WHICH EXCEED EIGHT (8) VERTICAL FEET, SHOULD BE STABILIZED WITH SYNTHETIC OR VEGETATIVE MATS. IN ADDITION TO HYDRO-SEEDING, IT MAY BE NECESSARY TO INSTALL TEMPORARY SLOPE DRAINS DURING CONSTRUCTION. TEMPORARY BERMS MAY BE NEEDED UNTIL THE SLOPE IS BROUGHT TO GRADE.
- STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED, BUT IN NO CASE MORE THAN FOURTEEN (14) DAYS AFTER WORK HAS CEASED, EXCEPT AS STATED BELOW.
- A. WHERE STABILIZATION IS PRECLUDED BY SNOW COVER OR FROZEN GROUND CONDITIONS STABILIZATION MEASURES MUST BE INITIATED AS SOON AS PRACTICABLE.
- B. WHERE CONSTRUCTION ACTIVITY ON A PORTION OF THE SITE IS TEMPORARILY CEASED, AND EARTH-DISTURBING ACTIVITIES WILL BE RESUMED WITHIN 14 DAYS, TEMPORARY STABILIZATION MEASURES DO NOT HAVE TO BE INITIATED ON THAT PORTION OF THE SITE.
- ALL SEDIMENT AND EROSION CONTROL DEVICES SHALL BE INSPECTED ONCE EVERY CALENDAR WEEK. IF PERIODIC INSPECTION OR OTHER INFORMATION INDICATES THAT A BMP HAS BEEN INAPPROPRIATELY OR INCORRECTLY PLACED, THE PERMITTEE MUST ADDRESS THE NECESSARY REPLACEMENT OR MODIFICATION REQUIRED TO CORRECT THE BMP WITHIN 48 HOURS OF IDENTIFICATION.
- PROVIDE SILT FENCE AND/OR OTHER CONTROL DEVICES, AS MAY BE REQUIRED, TO CONTROL SOIL EROSION DURING UTILITY CONSTRUCTION. ALL DISTURBED AREAS SHALL BE CLEANED, GRADED, AND STABILIZED WITH GRASSING IMMEDIATELY AFTER THE UTILITY INSTALLATION. FILL, COVER, AND TEMPORARY SEEDING AT THE END OF EACH DAY ARE RECOMMENDED. IF WATER IS ENCOUNTERED WHILE TRENCHING, THE WATER SHOULD BE FILTERED TO REMOVE ANY SEDIMENTS BEFORE BEING PUMPED BACK INTO ANY WATERS OF THE STATE PER THE ENVIRONMENTAL PLANS.
- ALL EROSION CONTROL DEVICES SHALL BE PROPERLY MAINTAINED DURING ALL PHASES OF CONSTRUCTION UNTIL THE COMPLETION OF ALL CONSTRUCTION ACTIVITIES AND ALL DISTURBED AREAS HAVE BEEN STABILIZED. ADDITIONAL CONTROL DEVICES MAY BE REQUIRED DURING CONSTRUCTION IN ORDER TO CONTROL EROSION AND/OR OFFSITE SEDIMENTATION. ALL TEMPORARY CONTROL DEVICES SHALL BE REMOVED ONCE CONSTRUCTION IS COMPLETE AND THE SITE IS STABILIZED.
- THE CONTRACTOR MUST TAKE NECESSARY ACTION TO MINIMIZE THE TRACKING OF MUD ONTO PAVED ROADWAY(S) FROM CONSTRUCTION AREAS AND THE GENERATION OF DUST. THE CONTRACTOR SHALL DAILY REMOVE MUDSOIL FROM PAVEMENT, AS MAY BE REQUIRED.
- TEMPORARY DIVERSION BERMS AND/OR DITCHES WILL BE PROVIDED AS NEEDED DURING CONSTRUCTION TO PROTECT WORK AREAS FROM UPSLOPE RUNOFF AND/OR TO DIVERT SEDIMENT-LADEN WATER TO APPROPRIATE TRAPS OR STABLE OUTLETS.
- ALL WATERS OF THE STATE (WOS), INCLUDING WETLANDS, ARE TO BE FLAGGED OR OTHERWISE CLEARLY MARKED IN THE FIELD. A DOUBLE ROW OF SILT FENCE IS TO BE INSTALLED IN ALL AREAS WHERE A 50-FOOT BUFFER CAN'T BE MAINTAINED BETWEEN THE DISTURBED AREA AND ALL WOS. A 10-FOOT BUFFER SHOULD BE MAINTAINED BETWEEN THE LAST ROW OF SILT FENCE AND ALL WOS.
- LITTER, CONSTRUCTION DEBRIS, OILS, FUELS, AND BUILDING PRODUCTS WITH SIGNIFICANT POTENTIAL FOR IMPACT (SUCH AS STOCKPILES OF FRESHLY TREATED LUMBER) AND CONSTRUCTION CHEMICALS THAT COULD BE EXPOSED TO STORM WATER MUST BE PREVENTED FROM BECOMING A POLLUTANT SOURCE IN STORM WATER DISCHARGES.
- A COPY OF THE SWPPP INSPECTION RECORDS, AND RAINFALL DATA MUST BE RETAINED AT THE CONSTRUCTION SITE OR A NEARBY LOCATION EASILY ACCESSIBLE DURING NORMAL BUSINESS HOURS, FROM THE DATE OF COMMENCEMENT OF CONSTRUCTION ACTIVITIES TO THE DATE THAT FINAL STABILIZATION IS REACHED.
- INITIATE STABILIZATION MEASURES ON ANY EXPOSED STEEP SLOPE (3H:1V OR GREATER) WHERE LAND-DISTURBING ACTIVITIES HAVE PERMANENTLY OR TEMPORARILY CEASED, AND WILL NOT RESUME FOR A PERIOD OF SEVEN (7) CALENDAR DAYS.
- MINIMIZE SOIL COMPACTION AND, UNLESS INFEASIBLE, PRESERVE TOPSOIL.
- MINIMIZE THE DISCHARGE OF POLLUTANTS FROM EQUIPMENT AND VEHICLE WASHING, WHEEL WASH WATER, AND OTHER WASH WATERS. WASH WATERS MUST BE TREATED IN A SEDIMENT BASIN OR ALTERNATIVE CONTROL THAT PROVIDES EQUIVALENT OR BETTER TREATMENT PRIOR TO DISCHARGE.
- MINIMIZE THE DISCHARGE OF POLLUTANTS FROM DEWATERING OF TRENCHES AND EXCAVATED AREAS. THESE DISCHARGES ARE TO BE Routed THROUGH APPROPRIATE BMPs (SEDIMENT BASIN, FILTER BAG, ETC.).
- THE FOLLOWING DISCHARGES FROM SITES ARE PROHIBITED:
  - WASTEWATER FROM WASHOUT OF CONCRETE, UNLESS MANAGED BY AN APPROPRIATE CONTROL;
  - WASTEWATER FROM WASHOUT AND CLEANOUT OF STUCCO, PAINT, FORM RELEASE OILS, CURING COMPOUNDS AND OTHER CONSTRUCTION MATERIALS;
  - FUELS, OILS, OR OTHER POLLUTANTS USED IN VEHICLE AND EQUIPMENT OPERATION AND MAINTENANCE; AND
  - SOAPS OR SOLVENTS USED IN VEHICLE AND EQUIPMENT WASHING.
- AFTER CONSTRUCTION ACTIVITIES BEGIN, INSPECTIONS MUST BE CONDUCTED AT A MINIMUM OF AT LEAST ONCE EVERY CALENDAR WEEK AND MUST BE CONDUCTED UNTIL FINAL STABILIZATION IS REACHED ON ALL AREAS OF THE CONSTRUCTION SITE.
- IF EXISTING BMPs NEED TO BE MODIFIED OR IF ADDITIONAL BMPs ARE NECESSARY TO COMPLY WITH THE REQUIREMENTS OF THIS PERMIT AND/OR SC'S WATER QUALITY STANDARDS, IMPLEMENTATION MUST BE COMPLETED BEFORE THE NEXT STORM EVENT WHENEVER PRACTICABLE. IF IMPLEMENTATION BEFORE THE NEXT STORM EVENT IS IMPRACTICABLE, THE SITUATION MUST BE DOCUMENTED IN THE SWPPP AND ALTERNATIVE BMPs MUST BE IMPLEMENTED AS SOON AS REASONABLY POSSIBLE.
- A PRE-CONSTRUCTION CONFERENCE MUST BE HELD FOR EACH CONSTRUCTION SITE WITH AN APPROVED ON-SITE SWPPP PRIOR TO THE IMPLEMENTATION OF CONSTRUCTION ACTIVITIES. FOR NON-LINEAR PROJECTS THAT DISTURB 10 ACRES OR MORE, THIS CONFERENCE MUST BE HELD ON-SITE UNLESS THE DEPARTMENT HAS APPROVED OTHERWISE.

## EXISTING UTILITIES AND FACILITIES

- THE LOCATION AND DESCRIPTIONS OF EXISTING UTILITIES SHOWN ON THE DRAWINGS ARE COMPILED FROM A COMBINATION OF AVAILABLE RECORDS AND/OR FIELD SURVEYS. THE ENGINEER OR UTILITY COMPANIES DO NOT GUARANTEE THE ACCURACY OR THE COMPLETENESS OF SUCH RECORDS. CONTRACTOR SHALL FIELD VERIFY LOCATIONS AND/OR DEPTHS AS NEEDED OF ALL EXISTING UTILITIES PRIOR TO CONSTRUCTION, EXERCISE EXTREME CAUTION WHEN WORKING NEAR EXISTING POWER, GAS, AND COMMUNICATIONS LINES.
- THE CONTRACTOR SHALL LOCATE AND MARK ALL EXISTING PROPERTY AND STREET MONUMENTS PRIOR TO CONSTRUCTION. ANY MONUMENTS DISTURBED DURING CONSTRUCTION OF THE PROJECT SHALL BE REPLACED BY A REGISTERED LAND SURVEYOR AT THE CONTRACTOR'S EXPENSE.
- THE CONTRACTOR SHALL CALL PALMETTO UTILITY PROTECTION SERVICE (PUPS) AND ANY LOCAL UTILITY COMPANY NOT REPRESENTED BY PUPS A MINIMUM OF 72 HOURS PRIOR TO STARTING ANY PROPOSED WORK (811).
- THE CONTRACTOR SHALL NOTIFY ALL APPLICABLE UTILITY AGENCY A MINIMUM 72 HOURS IN ADVANCE OF ANY EXCAVATION OR LAND DISTURBANCE NEAR EXISTING UTILITY LINES LOCATED ABOVE OR BELOW GROUND.
- UNLESS SPECIFICALLY STATED OTHERWISE, THE CONTRACTOR SHALL PROTECT AND MAINTAIN UTILITY SERVICES TO ALL EXISTING BUILDINGS AT ALL TIMES. IF THE CONTRACTOR REQUIRES AN INTERRUPTION TO ANY UTILITY SERVICE, THEY MUST NOTIFY THE EXISTING PROPERTY OWNER, THE APPLICABLE AGENCY, THE PROJECT OWNER, AND ENGINEER IN WRITING A MINIMUM OF 72 HOURS PRIOR TO THE DESIRED INTERRUPTION TO COORDINATE AND SCHEDULE TEMPORARY DISRUPTIONS AND RECONNECTION OF UTILITIES.

- ALL UTILITY CROSSINGS SHALL BE POTHOLED PRIOR TO EXCAVATING OR BORING TO ALLOW THE CONTRACTOR TO PREVENT GRADE OR ALIGNMENT CONFLICTS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR IDENTIFYING POTENTIAL UTILITY CONFLICTS FAR ENOUGH AHEAD OF CONSTRUCTION TO MAKE NECESSARY GRADE MODIFICATION WITHOUT DELAYING THE WORK. IF GRADE MODIFICATION IS NECESSARY, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE DESIGN ENGINEER. THE DESIGN ENGINEER SHALL OBTAIN APPROVAL FROM THE OWNER AND UTILITY COMPANY HAVING JURISDICTION.

- RELOCATION, REMOVAL, OR ABANDONMENT OF EXISTING UTILITIES OWNED/MAINTAINED BY OTHER AGENCIES (WATER, SEWER, GAS, POWER, COMMUNICATIONS, ETC.) SHALL BE COORDINATED BY THE CONTRACTOR.
- ANY MODIFICATION TO UTILITY LAYOUT, MATERIALS, ETC. SHALL BE COORDINATED WITH AND APPROVED BY THE DESIGN ENGINEER AND APPLICABLE AGENCY PRIOR TO ORDERING MATERIALS OR MAKING ANY SUCH CHANGES.
- INTERFERING PORTIONS OF UTILITIES THAT ARE ABANDONED IN PLACE SHALL BE REMOVED BY THE CONTRACTOR TO THE EXTENT NECESSARY TO ACCOMPLISH THE WORK. THE CONTRACTOR SHALL PLUG THE REMAINING EXPOSED ENDS OF DEMOLISHED SERVICES AND ABANDONED UTILITIES.
- ALL EXISTING FACILITIES SHALL BE MAINTAINED IN-PLACE BY THE CONTRACTOR UNLESS OTHERWISE DEPICTED ON THE PLANS OR DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL TAKE ALL PRECAUTIONS NECESSARY TO SUPPORT, MAINTAIN, OR OTHERWISE PROTECT EXISTING UTILITIES AND OTHER FACILITIES NOT INDICATED TO BE REMOVED AT ALL TIMES DURING CONSTRUCTION. ALL EXISTING STRUCTURES, INCLUDING BUT NOT LIMITED TO SIGNS AND DRIVES DISTURBED DURING CONSTRUCTION THAT ARE NOT SHOWN TO BE PERMANENTLY DEMOLISHED SHALL BE RESTORED TO THEIR ORIGINAL CONDITION OR BETTER.
- THE CONTRACTOR SHALL REMOVE AND REPLACE ALL EXISTING SURFACE FEATURES (UNLESS INDICATED TO BE PERMANENTLY DEMOLISHED) NECESSARY FOR INSTALLATION / REMOVAL OR ALL UNDERGROUND AND ABOVE GROUND WORK AS INDICATED ON THESE PLANS AND IN THE SCOPE OF WORK. THIS SHALL INCLUDE BUT NOT BE LIMITED TO FENCES, CURB & GUTTER, LANDSCAPING, SIDEWALKS, AND PAVEMENT.
- ANY PAVEMENT DAMAGED DURING CONSTRUCTION THAT IS NOT INDICATED TO BE PERMANENTLY DEMOLISHED SHALL BE RESTORED TO ORIGINAL CONDITION OR BETTER. ANY BROKEN PAVEMENT EDGES SHALL BE SAW-CUT SMOOTH AND THE PAVEMENT REPLACED TO MATCH EXISTING GRADES.
- DRAINAGE PIPES DESTROYED DURING CONSTRUCTION (WHICH ARE NOT INDICATED TO BE PERMANENTLY DEMOLISHED) ARE TO BE REPLACED AT A MINIMUM WITH NEW CLASS III - WALL B REINFORCED CONCRETE PIPE COMPLYING WITH ASTM C70 OR WITH OTHER OWNER APPROVED EQUIVALENT PIPE MATERIAL. THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF SUCH INSTANCES TO ENSURE MATERIAL COMPATIBILITY WITH THE EXISTING SOIL CONDITIONS FOR THIS SITE.
- ANY TYPES OF WELLS, TANKS, PIPES, STRUCTURES ETC., ENCOUNTERED SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE OWNER AND ENGINEER. IN THE EVENT CONTAMINATED OR HAZARDOUS MATERIALS IS ENCOUNTERED, THE CONTRACTOR SHALL CONTACT THE OWNER AND ENGINEER IMMEDIATELY.

## GENERAL CONSTRUCTION NOTES

- CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE FEDERAL, STATE, LOCAL AND OTHER APPLICABLE AGENCY REGULATIONS.
- CONTRACTOR SHALL HOLD ALL PERMITS IN HAND PRIOR TO COMMENCEMENT OF WORK.
- THE CONTRACTOR MUST ACQUIRE COPIES OF ALL REQUIRED PERMITS, STAMPED APPROVED AGENCY PLANS, OS-SWPPP, AND OTHER SUCH REQUIRED DOCUMENTS TO KEEP ON SITE THROUGHOUT CONSTRUCTION FOR AGENCY INSPECTORS, THE OWNER, AND OTHER AUTHORIZED OFFICIALS.
- CONTRACTOR SHALL PROVIDE ALL BONDS AND INSURANCE REQUIRED BY PUBLIC AND/OR PRIVATE AGENCIES HAVING JURISDICTION.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONSTRUCTION MEANS AND METHODS, COMPLIANCE WITH OSHA REQUIREMENTS, SCOPE OF WORK, AND COMPLIANCE WITH ALL NECESSARY PERMITS.
- THE CONTRACTOR SHALL PERFORM ALL WORK NECESSARY TO COMPLETE THE PROJECT IN ACCORDANCE WITH THE APPROVED CONSTRUCTION PLANS AND SPECIFICATIONS INCLUDING SUCH INCIDENTALS AS MAY BE NECESSARY TO MEET APPLICABLE AGENCY REQUIREMENTS AND PROVIDE A COMPLETED PROJECT.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL LINES, GRADES AND CONSTRUCTION STAKING FOR THE PROJECT.
- THE CONTRACTOR SHALL ADVISE THE ENGINEER IF EXISTING GRADES THAT ARE TO REMAIN ARE IN CONFLICT WITH PROPOSED WORK, CAUSING LIMITATIONS IN DRAINAGE PERFORMANCE OR SIGNIFICANT CHANGES IN CONSTRUCTION LIMITS DEFINED WITH CUT OR FILL LIMITS AND SPECIFICALLY THAT WORK WHICH MAY RESULT IN ANY CONSTRUCTION TAKING PLACE OUTSIDE OF PROPOSED CONSTRUCTION LIMITS.
- THE CONTRACTOR SHALL NOTIFY AGENCIES HAVING JURISDICTION AS NECESSARY OF THE ANTICIPATED SCHEDULE FOR INSPECTIONS PRIOR TO CONSTRUCTION.
- THE CONTRACTOR SHALL PROVIDE AND MAINTAIN THEIR OWN TEMPORARY RESTROOM FACILITIES ON SITE FOR WORK CREW USE.
- ALL EXISTING ROADS SHOWN ON THE PLANS ARE PAVED UNLESS OTHERWISE NOTED.
- THE CONTRACTOR SHALL PROTECT AND/OR RESTORE ANY CONTRACTOR RELATED IMPROVEMENTS OR DAMAGE ON THE OWNER'S PROPERTY, EASEMENTS, OR ANY ADJOINING PROPERTIES TO MEET OR EXCEED EXISTING CONDITIONS.
- THE CONTRACTOR SHALL COMPLY WITH THE REQUIREMENTS OF THE NPDES PERMIT AND GUIDELINES OF THE SCDES BMP HANDBOOK DURING THE ENTIRE CONSTRUCTION PERIOD. SEDIMENT AND EROSION CONTROL BEST MANAGEMENT PRACTICES (BMPs) SHALL INCLUDE, BUT NOT BE LIMITED TO, SILT FENCES, BERMS, INLET PROTECTION, ETC. AS NEEDED OR AS DIRECTED BY THE ENGINEER.
- CLEAR AND GRUB WITHIN WORK LIMITS FOR ALL SURFACE VEGETATION, TREES, STUMPS, BRUSH, ROOTS, ETC. DO NOT DAMAGE OR REMOVE SIGNIFICANT TREES EXCEPT AS SHOWN ON THE DRAWINGS.
- DISPOSAL OF EXCESS EXCAVATED MATERIALS OFF-SITE AND HAULING OF FILL MATERIALS REQUIRED FOR CONSTRUCTION SHALL BE THE FULL RESPONSIBILITY OF THE CONTRACTOR.
- WHERE ROADWAY DITCHES AND DRAINAGE PIPES ARE DAMAGED OR DISTURBED, THE CONTRACTOR SHALL RE-LAY DRAINAGE PIPE TO ORIGINAL INVERT ELEVATIONS AND RE-GRADE DITCHES TO ESTABLISH POSITIVE DRAINAGE.
- AREAS DISTURBED BY CONSTRUCTION SHALL BE STABILIZED WITH GRASS, SOD, MULCH, ETC. PER PLANS AND DETAILS, OR AT THE DIRECTION OF THE ENGINEER AS MAY BE APPLICABLE.

## DEMOLITION NOTES:

- REMOVE AND TRANSPORT DEBRIS AND DEMOLITION MATERIALS FROM THE PROJECT SITE IN A MANNER THAT WILL PREVENT SPILLAGE ON ADJACENT SURFACES / AREAS AND DISPOSE OF PROPERLY.
- DO NOT ALLOW DEMOLISHED MATERIALS TO ACCUMULATE ON SITE.
- KEEP ADJACENT SURFACES FREE OF DIRT, DIRT AND DEBRIS CAUSED BY DEMOLITION. RETURN ADJACENT AREAS TO THE CONDITION EXISTING BEFORE DEMOLITION.
- NO BURNING SHALL BE ALLOWED ON THE PROJECT.

## GENERAL SEDIMENT AND EROSION CONTROL NOTES

- THE FOLLOWING EROSION CONTROL MEASURES SHALL BE IMPLEMENTED DURING THE INITIAL LAND DISTURBANCE PHASE.
  - THE CONSTRUCTION ENTRANCE(S) SHALL BE PLACED AS SHOWN ON THE PLANS.
  - IMMEDIATELY AFTER THE ESTABLISHMENT OF THE CONSTRUCTION ENTRANCE(S), ALL PERIMETER EROSION CONTROL AND STORM WATER MANAGEMENT DEVICES SHALL BE INSTALLED AS SHOWN ON THE INITIAL LAND DISTURBANCE PHASE CONSTRUCTION PLANS.
  - SILT FENCE, AS INDICATED, SHALL BE INSTALLED AT THE PERIMETER OF THE LAND DISTURBANCE. THE SILT FENCE SHALL BE KEPT ERECT AT ALL TIMES AND REPAIRED WHEN REQUESTED BY THE SITE INSPECTOR, OR OWNER'S REPRESENTATIVE. SILT SHALL BE REMOVED WHEN ACCUMULATION REACHES 1/2 HEIGHT OF THE BARRIER. THE PERIMETER SILT FENCE SHALL BE INSPECTED DAILY FOR ANY FAILURES. ANY FAILURES OF FENCING SHALL BE REPAIRED IMMEDIATELY.
  - INLET PROTECTION MEASURES SHALL BE INSTALLED ON ALL EXISTING STORM DRAINAGE STRUCTURES AS INDICATED.
  - SEDIMENT TUBES SHALL BE INSTALLED IN AREAS OF CONCENTRATED FLOWS AS INDICATED.
  - CONTRACTOR SHALL PERFORM Dewatering WITH APPROPRIATE BMPs IN A MANNER THAT MEETS LOCAL AND STATE REGULATIONS WITH REGARD TO DISPOSAL PATH.
  - TEMPORARY DIVERSION DITCHES SHALL BE INSTALLED TO DIRECT FLOW TO TRAP UNTIL ROUGH GRADING RE-DIRECTS FLOWS TO FINAL DESIGN PATH.
  - NO BURN OR BURY PITS SHALL BE PERMITTED ON THE CONSTRUCTION SITE.
  - TEMPORARY SEEDING SHALL BE INSTALLED ON ALL EXPOSED AREAS WITHIN 14 DAYS OF LAND DISTURBANCE CEASING.
  - SILT FENCE SHALL BE PLACED AT THE TOE OF ALL DIRT STOCK PILE AREAS.

- SEDIMENT AND EROSION CONTROL MEASURES SHALL BE CHECKED AFTER EACH RAIN EVENT AND AT THE END OF EACH WORKING DAY. EACH DEVICE IS TO BE MAINTAINED OR REPLACED IF THE SEDIMENT ACCUMULATION HAS REACHED 1/2 HEIGHT OR THE CAPACITY OF THE DEVICE, AS APPLICABLE.

- THE CONSTRUCTION ENTRANCE(S) SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOW OF MUD ONTO PAVED AREAS. ALL MATERIALS SPILLED, DROPPED, WASHED OR TRACKED FROM VEHICLES ONTO PAVED AREAS OR INTO STORM DRAINAGE SHALL BE IMMEDIATELY REMOVED.

- EROSION CONTROL MEASURES SHALL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF EROSION CONTROL MEASURES INDICATED DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED AS DIRECTED BY THE SITE INSPECTOR OR OWNER'S REPRESENTATIVE.

- THE SITE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE OF ALL EROSION CONTROL MEASURES INCLUDING REPLACING OR REPAIRING ANY DAMAGED DEVICES.

- THE CONTRACTOR SHALL MAINTAIN CAREFUL SCHEDULING TO LIMIT THE AMOUNT OF LAND STRIPPED OF ITS NATURAL COVER AND, THEREFORE, LIMIT DURATION OF EXPOSURE BEFORE STABILIZATION COVER IS ESTABLISHED.

- SEDIMENT SHALL NOT BE WASHED INTO INLETS. ACCUMULATED SEDIMENT SHALL BE REMOVED AND RE-PLACED ON-SITE AND STABILIZED IN SUCH A MANNER THAT IT DOES NOT ACCUMULATE AGAIN.

- EROSION CONTROL DEVICES SHALL BE INSTALLED IMMEDIATELY AFTER GROUND DISTURBANCE REQUIRED FOR INSTALLATION HAS OCCURRED AND BEFORE ADJACENT CLEARING IS BEGUN. THE LOCATION OF SOME EROSION CONTROL DEVICES MAY NEED TO BE ALTERED FROM THAT SHOWN ON THE PLANS IF DRAINAGE PATTERNS DEVIATE FROM THOSE PROPOSED. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ACCOMPLISH EROSION CONTROL FOR ALL DRAINAGE PATTERNS CREATED AT VARIOUS STAGES DURING CONSTRUCTION. ANY DIFFICULTY IN CONTROLLING EROSION DURING ANY PHASE OF CONSTRUCTION SHALL BE REPORTED TO THE OWNER'S REPRESENTATIVE.

- CUT AND FILL SLOPES SHALL NOT EXCEED 3H:1V IN ALL LOCATIONS UNLESS INFEASIBLE.

- THE CONTRACTOR SHALL MAINTAIN ALL PONDS, SEDIMENT BASINS, AND EROSION CONTROL MEASURES UNTIL PERMANENT GROUND COVER IS ESTABLISHED. SEDIMENT SHALL BE REMOVED FROM BASINS WHEN IT REACHES THE HALFWAY POINT ON THE RISER.

- ALL ROADWAY AND PARKING SHOULDER SHALL HAVE VEGETATIVE COVER ESTABLISHED AS SOON AS FINAL GRADE IS ACHIEVED BEHIND CURBS.



- UPON COMPLETION OF THE PROJECT AND AUTHORIZATION FROM THE AUTHORITY HAVING JURISDICTION, THE CONTRACTOR SHALL REMOVE ALL TEMPORARY EROSION CONTROL MEASURES AND PROPERLY DISPOSE OF THEM UNLESS OTHERWISE NOTED.

## SEQUENCE OF CONSTRUCTION

- RECEIVE LETTER OF EXEMPTION FROM SCDES.
- INSTALL CONSTRUCTION ENTRANCE(S) AND BEGIN MAINTENANCE OF SEDIMENT CONTROLS AS NECESSARY. CONTINUE MAINTENANCE UNTIL ALL FINAL STABILIZATION MEASURES ARE IN PLACE AND REMOVAL OF CONTROLS IS APPROVED BY THE AUTHORITY HAVING JURISDICTION.
- CLEAR AND GRUB FOR THE INSTALLATION OF PERIMETER CONTROLS.
- INSTALL PERIMETER CONTROLS AND TREE PROTECTION AS APPLICABLE.
- DEMOLISH AND REMOVE EXISTING STRUCTURES, HARDCAPES, AND DEBRIS AS APPLICABLE.
- CLEAR AND GRUB THE REMAINDER OF THE DISTURBED AREA.
- COMPLETE GRADING.
- CONSTRUCT PROPOSED BUILDING
- COMPLETE SITE SURFACE IMPROVEMENTS INCLUDING CURBS, PAVEMENT, ETC.
- ESTABLISH PERMANENT SOIL STABILIZATION.
- REMOVE TEMPORARY SEDIMENT AND EROSION CONTROL MEASURES AFTER THE ENTIRE AREA FLOWING TO EACH MEASURE IS PERMANENTLY STABILIZED AND APPROVED BY THE ENGINEER AND THE AUTHORITY HAVING JURISDICTION.

## DRAINAGE FACILITIES MAINTENANCE PLAN


- TEMPORARY SEDIMENT CONTROLS:
  - THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL MAINTENANCE INCLUDING BUT NOT NECESSARILY LIMITED TO:
    - DURING CONSTRUCTION UNTIL FINAL ACCEPTANCE BY THE AUTHORITIES HAVING JURISDICTION:
      - DAILY:
        - OBSEVING PAVED AREAS THAT ARE UTILIZED FOR SITE ACCESS TO LOOK FOR SIGNS OF SOIL BEING TRACKED FROM THE SITE AND TAKING CORRECTIVE ACTION AS NECESSARY
        - CORRECTING ANY DAMAGE TO TEMPORARY SEDIMENT CONTROLS AS SOON AS POSSIBLE WHEN IT OCCURS.
      - WEEKLY:
        - INSPECTING TEMPORARY SEDIMENT CONTROLS FOR DAMAGE AND ACCUMULATED SEDIMENT. REMOVING SEDIMENT AND REPAIRING OR REPLACING DAMAGED TEMPORARY SEDIMENT CONTROLS AS NECESSARY.
        - EVALUATING PERFORMANCE AND AMENDING, MODIFYING, IMPROVING, OR RELOCATING TEMPORARY SEDIMENT CONTROLS AS NECESSARY.
        - LOGGING INSPECTION OBSERVATIONS, RECOMMENDATIONS, REPAIRS, RELOCATIONS, AMENDMENTS, AND IMPROVEMENTS AS NECESSARY
      - BI-WEEKLY:
        - EVALUATING SITE AND INSTALLING PERMANENT LANDSCAPING OR TEMPORARY SEEDING AS NECESSARY.
    - AT COMPLETION OF CONSTRUCTION (UPON FINAL ACCEPTANCE BY AUTHORITIES HAVING JURISDICTION)
      - REMOVING OF ALL TEMPORARY SEDIMENT CONTROLS.



KATEWAY PROPERTIES LLC.  
DB. 904 - PG. 001  
PB. - PG. 64-78  
TAX MAP NO: 6856-896-325

ROSALYN DANSBY  
DB. 1638 - PG. 1303  
PB. - PG. 99-32  
MAP NO: 6856-947-406

DB. 1027 - PG. 214  
PB. - PG. 82-102  
TAX MAP NO: 6856-939-



## GENERAL LEGEND

PROPERTY LINE	— - - - -
LIMITS OF DISTURBANCE	— LOD — LOD —
VEGETATION LINES	— ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
HEAD ELECTRICAL LINES	— OHP — OHP —
UTILITY POLE	○ UP
GUY ANCHOR	←
RING LOCATION	○
ASPHALT PAVEMENT	[Hatched Box]
CALCULATED POINT	△

## DEMOLITION LEGEND

ASPHALT TO BE REMOVED


## EXISTING CONDITIONS AND DEMOLITION NOTES:

1. UTILITIES AS SHOWN ARE BASED ON APPARENT AND OBVIOUS SURVEYED UTILITY FEATURES, AND GREENWOOD COUNTY GIS MAPPING. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING UTILITIES PRIOR TO CONSTRUCTION AND SHALL NOTIFY THE ENGINEER OF ANY DISCREPANCIES.
2. SURVEY WAS PERFORMED BY DAVIS & FLOYD, INC.
3. ALL UTILITIES NOT SPECIFIED TO BE DEMOLISHED SHALL REMAIN UNDISTURBED.
4. PRIOR TO BEGINNING DEMOLITION, THE CONTRACTOR SHALL ENSURE THAT PHASE 1 SEDIMENT AND EROSION CONTROL MEASURES ARE INSTALLED (CONSTRUCTION ENTRANCE & PERIMETER SILT FENCE).
5. ALL DEMOLITION INCLUDES PROPER REMOVAL AND DISPOSAL OF MATERIAL BY CONTRACTOR.
6. CONTRACTOR SHALL TAKE CARE TO PROTECT ALL STRUCTURES, PAVEMENT, VEGETATION, ETC. THAT IS NOT IDENTIFIED TO BE DEMOLISHED. CONTRACTOR SHALL REPAIR/REPLACE ANY DAMAGE CAUSED DURING CONSTRUCTION TO EXISTING CONDITIONS OR BETTER.
7. NO BURNING SHALL BE ALLOWED ON THE PROJECT SITE.



ow what's below.  
**Call** before you dig.

## PROJECT DATUM INFORMATION:



PIEDMONT TECHNICAL COLLEGE  
GREENWOOD, SOUTH CAROLINA




# XISTING CONDITIONS AND DRAWING TITLE

PIEDMONT TECHNICAL COLLEGE  
GREENWOOD, SOUTH CAROLINA


# XISTING CONDITIONS AND DRAWING TITLE

NO.	RELEASED	DATE
014341.00	1 BID DOCUMENTS	JDC 11/25/2025
DATE		
APRIL 2025		
DESIGNED		
AMK		
DRAWN		
AMK		
CHECKED		
JDC		
APPROVED		
JDC		





NO.	RELEASED	CHECKED	DATE
014341.00	1 BID DOCUMENTS	JDC	11/25/2025
DATE			
APRIL 2025			
DESIGNED			
AMK			
DRAWN			
AMK			
CHECKED			
JDC			
APPROVED			
AMK			



COPYRIGHT © 2025 CRAIG GAULDEN & DAVIS, INC.  
ALL RIGHTS RESERVED

THIS COPYRIGHTED DOCUMENT AND ALL  
INFORMATION CONTAINED HEREIN IS AN  
INSTRUMENT OF SERVICE AND SHALL NOT BE  
REPRODUCED, ALTERED, OR REUSED IN PART OR  
IN WHOLE WITHOUT PRIOR WRITTEN PERMISSION  
FROM THE ARCHITECT. THIS DRAWING IS THE  
EXCLUSIVE PROPERTY OF THE ARCHITECT AND  
MUST BE RETURNED UPON REQUEST.

PROJECT  
A NEW DRY STORAGE BUILDING

## PIEDMONT TECHNICAL COLLEGE


OSE # H59-N309-TM  
GREENWOOD, SC

MARK	DATE	DESCRIPTION

ISSUE: BID DOCUMENTS  
DATE: 11/25/25  
PROJECT NO: 25010  
DRAWN BY: DLD  
CHECKED BY: DLD


## PEMB DETAILS

A101




**SIDE ELEVATION**  
3  
A101  
1 / 8 " = 1'-0"

**FRONT / REAR ELEVATION**  
2  
A101  
1 / 8 " = 1'-0"



**TYPICAL WALL SECTION**  
4  
A101  
1 / 2 " = 1'-0"



**FLOOR PLAN**  
1  
A101  
1 / 8 " = 1'-0"



PALMETTO STRUCTURAL  
ENGINEERING, LLC  
104 Hunter Hill Circle  
Six Mile, SC 29682  
(c) 864-436-8684  
Ryan@PalmettoSE.com



Project:  
Piedmont Technical  
College  
Dry Storage Bldg.

Greenwood County, SC


REVISIONS	Description	Bid Documents
No. A Date 11-25-25		

Architect:  
**CRAIG GAULDEN DAVIS**  
• Architecture  
Planning  
Interiors  
19 Washington Park  
Greenville, SC 29601  
Phone: 864-242-0761  
Fax: 864-242-0762  
E-mail: cgd@cgadavis.com

Foundation / Slab  
Plan, Sections  
Scale: As Noted  
Date: 11-25-25  
Drawn By: R. Summey  
Project No.:  
Sheet:



**S-1**

Sheet 1 of 1




**A FOUNDATION/ SLAB PLAN**

Foundation Schedule			
TYPE	WIDTH X LENGTH	THICKNESS	REINFORCING
F33T	3'-0" x 3'-0"	16" THKD SLAB	(3) #4 EA WAY
F44T	4'-0" x 4'-0"	16" THKD SLAB	(5) #5 EA WAY, TOP & BOTTOM MAT
F64T	6'-0" x 4'-0"	24" THKD SLAB	(7) #6 EA WAY, TOP & BOTTOM MAT



**1 SECTION**

**2 SECTION**



**B ANCHOR ROD DETAIL**

01000 GENERAL

- The structure reflected on the drawings is structurally sound in its completed condition only. The design of any and all temporary shoring and bracing prior to the completed condition shall be the contractor's responsibility. The Structural Engineer of Record (EOR) shall not be responsible for the means, methods, techniques, sequences, procedures nor safety programs which are employed by the contractor to build the completed structure. Any deviations from the completed structure represented in the drawings must be submitted to the EOR for approval in writing.
- The Contractor shall verify all conditions including existing structures (above and below grade) and shall notify of the EOR of any discrepancies. The Contractor shall perform all required field measurements.
- The Sections and Details shown shall be considered to be typical for all similar conditions. The Contractor shall submit written Requests for Information for areas in question.
- The Contractor shall submit shop drawings for each of the structural components shown on the drawings. Four copies of the shop drawings shall be submitted to the Architect for distribution.
- The Contractor shall locate Anchor Rod locations with using the metal building drawings. Design of diameter of rod is by the metal building designer. Projection of rod is by metal building designer; embedment is by Palmetto Structural Engineering, LLC.
- Foundations shown are based on preliminary Building Manufacturer drawings. For Construction drawings shall be provided by the general contractor prior to construction for confirmation of the foundations shown.
- Palmetto Structural Engineering, LLC was contracted to provide slab and foundation design only using the building supplier's anchor setting plan and reactions. PSE did not review building framing or finishes.

01400 QUALITY CONTROL SERVICES:


- A Testing Agency shall be retained by the Owner to perform necessary testing as required by Chapter 17 of the International Building Code. In addition, the testing agency, at the owner's expense, shall perform the following minimum tests. The Contractor shall provide shop drawings, specifications, and design drawings to the testing agency. Testing reports shall be submitted to the EOR within two weeks of performing the tests.
- Earthwork: Footing subgrades and fill placements to be reviewed and tested. Frequency of testing to be determined by the geotechnical engineer.
- Concrete: Testing agency shall inspect placement of all reinforcing as shown on drawings and schedules. Concrete testing shall be in accordance with ACI 301 and applicable ASTM standards. The following tests should be performed for each day's first load and each 100 cubic yards:
  - Weight of concrete, ASTM C 138.
  - Slump, ASTM C 143.
  - If required, Air content of freshly mixed concrete by pressure method, ASTM C 231 or volumetric method, ASTM C 173.
  - Concrete temperature at placement time.
  - Air temperature and weather (windy, cloudy, etc) at placement time.
  - Strength determined in accordance with ASTM C 39.
  - Slab F1 and F2 shall be evaluated.

03000 FOUNDATIONS:

- The Contractor shall notify the EOR of any below grade structure which may affect the foundation performance.
- Foundations shall bear on residual soils or engineered fill capable of supporting an allowable pressure of 3000 psf. Soils shall be stable, and any expansive, compressible, or shifting material shall be removed to ensure a stable moisture content. Slabs on grade are designed for a modulus of subgrade reaction of 175 pci using a K = 30.

03300 CAST-IN-PLACE CONCRETE:

- All concrete work and materials shall be in accordance with ACI 318 and ACI 301.
- Minimum Material Specifications:
  - Portland Cement: ASTM C150, Type 1
  - Fly Ash: ASTM C 618, Type F (limit to 20% of cementitious content)
  - Maximum water/cementitious material ratio: 0.5
  - No water may be added at the site without consent of the engineer.
- Slabs-on-grade:
  - Interior slabs-on-grade and foundations shall have a 28 day compressive strength of 4000 ps.
  - Interior slabs to receive a hard steel trowel finish with overall  $F_t = 35$  and  $F_t = 25$ , and minimum local values of  $F_t = 24$  and  $F_t = 17$  shall be tested/confirmed by testing agency.
  - Exterior slabs (under roof or floor) shall have air entraining admixture to provide 6% entrained air. Chamfer all exposed slab edge corners (3/4").
  - Slabs shall be cured using a curing compound containing 30% solids following the manufacturer's specifications. Curing compound shall be compatible with floor finishes.
  - Vapor barrier under slab shall meet permeability requirements of the floor finishes. As a minimum, a 10 mil vapor barrier is required, lapping and sealing all seams.
  - Provide sawcut control joints or construction joints at 12'-0" (maximum square pattern (see slab plan for other requirements). Cut 1" joints as soon as possible after finishing (within 12 hours of placement). Construction joints shall be formed by thickening the slab to 8" within 18" of the joint and installing a continuous key or 3/4" dowels at 18" o.c. Joint filler specification to be by owner or architect.
  - Welded Wire Fabric (ASTM A185) (if specified in slabs on grade) shall be installed 1" from the top face of the slab, lapping edges 6". WWF to be supplied in sheet stock only.
  - Provide isolation joints at column boxouts, walls, and penetrations.
  - Reinforce at all re-entrant corner with no control joints with (2) #3 x 4'-0" long centered on the corner, located in the top of the slab. Reinforce around all pipe or box penetrations greater than 3" with (4) #3 in diamond pattern.
  - Specification of exterior concrete paving or sidewalks is by the Civil Engineer.
  - Concrete splatter on walls or adjacent slabs shall be removed.
- Reinforcing Steel:
  - All detailing, fabrication, and placing shall be in accordance with ACI 315.
  - Reinforcing steel shall be new billet bars conforming to ASTM A615, grade 60.
  - Provide 3" concrete cover for all concrete cast against earth.



**D HAIRPIN DETAIL**

1" = 1'-0"

SEE BLDG DWGS FOR BOLT DIMENSIONS

**Structural Design Criteria**

**Structure Type**  
Pre-Engineered Metal Building with Ordinary Steel Moment Frames & Concentrically Braced Steel Frames.

**Building Code**  
2021 International Building Code

**Building Use**  
Building Category 2.

**Vertical Loads**

Dead Loads of Roof  
See Pre-Engineered Metal Building Drawings

Live Loads at Roof  
Occupancy (Reducible for Slope, Area) 20 psf

Snow Loads  
Ground Snow Load 10 psf

Design Snow Load 7.7 psf

**Lateral Loads**

Wind Loads  
Velocity (3-Second Gust), Ultimate Exposure 110 mph

C

Seismic Loads  
USCS Mapped 1 second Spectral Response, S1 10%

USCS Mapped short term Spectral Response, S2 30%

Spectral Response, S3 D

Site Class (Assumed) Response Modification Coefficient See PEMB Dwgs.

Spectral Response, Sds See PEMB Dwgs.

Spectral Response, Sd1 See PEMB Dwgs.

Spectral Response Coefficient, Cs See PEMB Dwgs.

Design Category C

Analysis Type ELF

Base Shear See PEMB Dwgs.


Scale: As Noted  
Date: 11-25-25  
Drawn By: R. Summey  
Project No.:  
Sheet:

**S-1**

EXHAUST FAN SCHEDULE										
EQUIPMENT TAG	MANUFACTURER	MODEL	AIRFLOW	E.S.P. (IN. WC)	FAN RPM	DRIVE	MOTOR WATTS OR HP	SONES	ELECTRICAL (V/PH/Hz)	ACCESSORIES
EF-1	GREENHECK.	BAER-36	10,000	0.25	821	BELT	2 HP	27	208/1/60	1,2,3,4,5
EQUAL PRODUCTS BY PENN-BARY, COOK, TWIN CITY.										
ACCESSORIES: 1. CAST ALUMINUM OR FABRICATES STEEL FAN BLADES. 2. PILLOW BLOCK BEARINGS. 3. BELT DRIVE 4. FAN HOUSING, MOTOR GUARD, BACKDRAFT DAMPER, DISCHARGE HOOD, BIRD SCREEN. 5. FACTORY DISCONNECT										

① HVAC Plan  
1/4" = 1'-0"

LOUVER SCHEDULE									
MARK	MANUFACTURER	MODEL	SIZE	ACCESSORIES					
L-1	POTTORF	EXD637	48x48	1,2,3					
L-2	POTTORF	EXD637	48x48	1,2,3					
EQUAL PRODUCTS BY: GREENECK, RUSKIN									
ACCESSORIES: 1. BIRD SCREEN 2. KYNAR 500 FINISH (COLOR SELECTED BY ARCHITECT) 3. WITH MOTORIZED DAMPER WITH 120 VOLT DAMPER ACTUATOR.									





CRAIG  
GAULDEN  
DAVIS PBK

• Architecture  
Planning  
Interiors

19 Washington Park  
Greenville, SC 29601

Phone 864.424.0761  
Fax 864.501.9945  
E-mail cgd@cgdarch.com



COPYRIGHT © 2025 CRAIG GAULDEN & DAVIS, INC.  
ALL RIGHTS RESERVED

THIS COPYRIGHTED DOCUMENT AND ALL  
INFORMATION CONTAINED HEREIN IS AN  
INSTRUMENT OF SERVICE AND SHALL NOT BE  
REPRODUCED, ALTERED, OR REUSED IN PART OR  
IN WHOLE WITHOUT PRIOR WRITTEN PERMISSION  
FROM THE OWNER. THIS DRAWING IS THE  
EXCLUSIVE PROPERTY OF THE ARCHITECT  
AND MUST BE RETURNED UPON REQUEST.

CONSULTANT

SE&C

HVAC • PLUMBING • FIRE PROTECTION  
STEPHENS ENGINEERING & CONSULTING, LLC  
130 HERITAGE LANE  
EASLEY, SC 29642  
(864) 414-1965

PROJECT

ALTERATIONS & ADDITIONS

PIEDMONT  
TECHNICAL  
COLLEGE


OSE #H59-N309-TM  
GREENWOOD, SC

DATE MARK DESCRIPTION

ISSUE: BID DOCUMENTS  
DATE: 11-25-2025  
PROJECT NO: 25010  
DRAWN BY: SCS  
CHECKED BY: SCS

HVAC PLAN

GENERAL NOTES:  
1. ALL WORK SHALL BE PER THE INTERNATIONAL MECHANICAL CODE (2021).  
2. ALL WORK SHALL BE COORDINATED WITH THE GC AND WITH ALL OTHER TRADES.



**PLUMBING GENERAL NOTES:**

1. ALL PLUMBING WORK SHALL BE IN ACCORDANCE WITH THE 2021 SOUTH CAROLINA PLUMBING CODE.
2. ALL WATER AND SEWER PIPING SHALL BE TESTED PER THE PLUMBING CODE.

**PLUMBING PIPING:**

1. ABOVE GROUND DOMESTIC WATER PIPING SHALL BE TYPE L HARD COPPER.
2. BELOW GROUND DOMESTIC WATER PIPING SHALL BE TYPE K HARD COPPER.
3. ALL WASTE AND VENT PIPING SHALL BE PVC, SCHEDULE 40 DWV PIPE AND FITTINGS.

**P101**

**CRAIG  
GAULDEN  
DAVIS PBK**

• Architecture  
Planning  
Interiors

19 Washington Park

Greenville, SC 29601

Phone 864.242.0761

Fax 864.501.9945

E-mail cgd@cgdarch.com



COPYRIGHT © 2025 CRAIG GAULDEN & DAVIS, INC.  
ALL RIGHTS RESERVED

THIS COPYRIGHTED DOCUMENT AND ALL  
INFORMATION CONTAINED HEREIN IS AN  
INSTRUMENT OF SERVICE AND SHALL NOT BE  
REPRODUCED, ALTERED, OR REUSED IN PART OR  
IN WHOLE WITHOUT PRIOR WRITTEN PERMISSION  
FROM THE OWNER. THIS DRAWING IS THE  
EXCLUSIVE PROPERTY OF THE ARCHITECT AND  
MUST BE RETURNED UPON REQUEST.

**CONSULTANT**

**SE&C**

HVAC • PLUMBING • FIRE PROTECTION  
STEPHENS ENGINEERING & CONSULTING, LLC  
130 HERITAGE LANE  
EASLEY, SC 29642  
(864) 414-1965

**PROJECT**

ALTERATIONS & ADDITIONS


**PIEDMONT  
TECHNICAL  
COLLEGE**

OSE #H59-N309-TM  
GREENWOOD, SC

DATE | MARK | DESCRIPTION


ISSUE: BID DOCUMENTS  
DATE: 11-25-2025  
PROJECT NO: 25010  
DRAWN BY: SCS  
CHECKED BY: SCS

**PLUMBING PLAN**



## ELECTRICAL SPECIFICATIONS


1. DRAWINGS ARE DIAGRAMMATIC AND INTENDED TO SHOW APPROXIMATE LOCATIONS. ELECTRICAL WORK SHALL NOT INTERFERE WITH CLEARANCES REQUIRED FOR GENERAL AND MECHANICAL CONSTRUCTION. ANY CORRECTIONS WILL BE MADE BY THE ELECTRICAL CONTRACTOR AT NO COST TO THE OWNER.
2. ALL WORK SHALL BE ACCOMPLISHED IN STRICT ACCORDANCE WITH THE IBC AND THE NATIONAL ELECTRICAL CODE, LATEST EDITIONS, AND ALL APPLICABLE STATE AND LOCAL CODES. ALL WORK SHALL BE ACCOMPLISHED IN A NEAT AND PROFESSIONAL MANNER.
3. ALL MATERIALS SHALL BE NEW AND SHALL BEAR THE U/L LABEL.
4. CONTRACTOR SHALL CONFIRM BRANCH CIRCUIT SIZING, LOCATIONS AND CONNECTION REQUIREMENTS FOR ALL MECHANICAL EQUIPMENT PRIOR TO INSTALLATION. REFERENCE MECHANICAL DRAWINGS FOR EQUIPMENT LOCATIONS AND VERIFICATION OF CIRCUIT SIZE. ANY ADJUSTMENTS REQUIRED SHALL BE MADE BY THE ELECTRICAL CONTRACTOR. SUBSTANTIAL CHANGES TO THESE PLANS SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT/ENGINEER.
5. ALL TERMINALS SHALL BE RATED FOR 75 DEGREES CELSIUS COPPER WIRE.
6. RECEPTACLES SHALL BE OF THE GROUNDING TYPE WITH GROUND CONNECTION MADE THROUGH AN EXTRAS POLE WHICH SHALL BE PERMANENTLY CONNECTED TO THE RACEWAY AND GROUNDING SYSTEMS. COVERPLATES FOR ALL WIRING DEVICES TO BE PLASTIC/STAINLESS STEEL. DETERMINE THE COLOR OF ALL WIRING DEVICES WITH ARCHITECT.
7. LIGHTING FIXTURES SHALL BE FURNISHED COMPLETE IN ALL RESPECTS PER FIXTURE SCHEDULE. VERIFY CEILING FINISHES AND SUSPENSION SYSTEMS FOR SELECTION OF PROPER TRIM AND SUPPORT ARRANGEMENTS. INSTALL ALL LIGHT FIXTURES WITH LAMPS AS REQUIRED.
8. LIGHTING FIXTURES SHALL BE SECURELY FASTENED TO THE STRUCTURE BY A MECHANICAL MEANS THAT COMPLIES WITH REQUIREMENTS FOR SEISMIC EVENTS PER ASCE 7-16.
9. ALL WIRING SHALL BE CONCEALED WHERE POSSIBLE AND INSTALLED IN SUITABLE RACEWAYS. EMT SHALL BE USED (3/4" MIN) FOR LIGHTING AND POWER BRANCH CIRCUITRY. EMT SHALL BE USED FOR EQUIPMENT FEEDERS. SCHEDULE 40 PVC SHALL BE USED UNDERGROUND.
10. RECEPTACLES INSTALLED BACK TO BACK IN FIRE RATED WALLS SHALL BE A MINIMUM OF 24" APART AND SHALL NOT OCCUPY THE SAME STUD CAVITY.
11. DISCONNECT SWITCHES SHALL BE FURNISHED AS SHOWN ON THE DRAWINGS WITH VOLTAGE RATING, AMPERE RATING AND NUMBER OF POLES AS INDICATED. PROVIDE NEMA 3R TYPE WHERE EXPOSED TO WEATHER. PROVIDE HEAVY DUTY TYPE SWITCHES.
12. FUSES FOR FUSIBLE SWITCHES SHALL BE OF THE DUAL ELEMENT, REJECTION TYPE.
13. DISCONNECT SWITCHES SHALL HAVE EXTERNAL SWITCH HANDLE, SWITCH AND DOOR SHALL BE INTERLOCKED SUCH THAT THE DOOR CAN NOT BE OPENED UNLESS THE SWITCH IS IN THE OPENED POSITION.
14. ALL WIRE SHALL BE SINGLE CONDUCTOR STRANDED, COPPER SIZED AS INDICATED ON THE DRAWINGS. MINIMUM SIZE SHALL BE #12 AWG.
15. SOLID WIRE MAY BE USED FOR #12 AND #10 AWG WIRE USED ON LIGHTING FIXTURES, RECEPTACLES AND SWITCHES ONLY.
16. INSULATION OF WIRE SHALL BE 75 DEGREES CELSIUS (THHN, THWN), 600 VOLT.
17. UNLESS INDICATED ON THE DRAWINGS, ALL WIRING SHALL BE #12 AWG. CONTRACTOR SHALL CONFIRM AND ROUTE THE PROPER QUANTITY OF WIRES AND SIZE OF CONDUIT TO FIT THE APPLICATION AND THE CIRCUITRY INDICATED.
18. CONTRACTOR SHALL PROVIDE A PROPERLY SIZED, GREEN COLORED INSULATED GROUNDING CONDUCTOR IN ALL CONDUITS. THIS CONDUCTOR IS NOT INDICATED IN THE HATCH MARKS ON THE CONDUIT RUNS ON THE PLANS.
19. INSTALL A COMPLETE GROUNDING SYSTEM IN ACCORDANCE WITH NEC ARTICLE 250 AND THESE SPECIFICATIONS. GROUNDING SYSTEM SHALL BE ELECTRICALLY CONTINUOUS THROUGHOUT.
20. CONTRACTOR IS RESPONSIBLE FOR COORDINATING WITH THE LOCAL POWER AND TELEPHONE UTILITY COMPANIES FOR ALL COST REQUIREMENTS AND METHODS FOR THE NEW SERVICES INDICATED. PROVIDE ALL MATERIALS AND LABOR AS DIRECTED BY THE LOCAL UTILITY SERVICES FOR A COMPLETE AND OPERABLE INSTALLATION.
21. PANELBOARDS SHALL BE PROVIDED WITH DISTRIBUTIVE PHASING AND RATINGS AND BREAKER REQUIREMENTS AS PER SCHEDULES. LABEL ALL PANELS AND PROVIDE TYPEWRITTEN CIRCUIT DIRECTORIES.
22. THE SHORT CIRCUIT RATING OF ALL SERVICE EQUIPMENT AND PANELBOARDS SHALL BE NO LESS THAN THAT INDICATED ON THE PANEL SCHEDULES UNLESS BEFORE PURCHASING EQUIPMENT, THE ELECTRICAL CONTRACTOR CONTACTS THE LOCAL UTILITY COMPANY PROVIDING SERVICE AND OBTAIN IN WRITING THE MAXIMUM SHORT CIRCUIT CURRENT SUPPLIED TO THE SERVICE EQUIPMENT. ALL EQUIPMENT SHALL BE RATED AND COORDINATED TO NO LESS THAN THAT SUPPLIED.
23. TRANSFORMERS SHALL BE FLOOR MOUNTED, GENERAL PURPOSE DRY TYPE AND OF THE KVA RATING AS INDICATED ON THE PLANS. ALL SHALL BE VENTILATED, 150°C TEMP RISE, CORE AND COIL ASSEMBLIES MOUNTED ON RUBBER ISOLATION PADS TO MINIMIZE THE SOUND LEVEL. SQUARE "D" CLASS 7410 SERIES OR EQUAL.



ELECTRICAL RISER DIAGRAM

1  
E0.2  
N.T.S.

PANELBOARD: "RP"		VOLTAGE: 120/208V, 3Ø, 4W									
MOUNTING: SURFACE		MAINS: MCB MIN. AIC RATING: 10,000A									
LOAD	DESCRIPTION	CKT.	TRIP	TRIP	CKT.	DESCRIPTION	LOAD	L1	L2	L3	PHASE LOAD VA
1080	L-WAREHOUSE	1	20	2	2	R-MOTORIZED DOOR	1000	2080			
1080	L-WAREHOUSE	3	20	20	4	R-MOTORIZED DOOR	1000		2080		
800	L-EXTERIOR	5	20	20	6	R-WAREHOUSE RECEPTS.	360			1160	
1200	WEF-1	7	20	20	8	R-WAREHOUSE RECEPTS.	360	1560			
1200		9	20	10	10	R-WAREHOUSE RECEPTS.	360		1560		
500	LV-1 & LV-2	11	20	20	12	SPARE					500
	SPARE	13	20	20	14	SPARE					
	SPARE	15	20	20	16	SPARE					
	SPARE	17	20	15	18	SPARE					
	SPARE	19	20	15	20	SPARE					
	SPARE	21	20	20	22	SPARE					
	SPARE	23	20	20	24	SPARE					
	SPACE	25			26	SPACE					
	SPACE	27			28	SPACE					
	SPACE	29			30	SPACE					
	SPACE	31			32	SPACE					
	SPACE	33			34	SPACE					
	SPACE	35			36	SPACE					
	SPACE	37			38	SPACE					
	SPACE	39			40	SPACE					
	SPACE	41			42	SPACE					



CONSULTANT



PROJECT

A NEW STORAGE BUILDING

**PIEDMONT  
TECHNICAL  
COLLEGE**

GREENWOOD, SC

ISSUE: BID DOCUMENTS  
DATE: 11/25/25  
PROJECT NO: 25-125  
DRAWN BY: RBP  
CHECKED BY: JDJ

ELECTRICAL LIGHT  
Fixture SCHEDULE


**E0.2**

**GENERAL LIGHTING NOTES:**

1. MANUFACTURERS & NUMBERS ARE LISTED TO ESTABLISH QUALITY ONLY AND NOT TO LIMIT COMPETITION. TEN DAYS PRIOR TO BIDDING, SUBSTITUTIONS ARE ALLOWED SUBJECT TO SUBMITTAL DATA, PHOTOMETRICS & ENGINEERS APPROVAL AS REQUIRED BY SPECIFICATIONS.
2. ALL FIXTURES TO BE U.L. LISTED. ALL EXTERIOR FIXTURES SHALL HAVE U.L. WET LABEL OR DAMP LABEL AS REQUIRED BY LOCATION. CONTRACTOR SHALL VERIFY BEFORE INSTALLING FIXTURE.
3. CONTRACTOR SHALL PROVIDE ALL MOUNTING ACCESSORIES, BAR HANGARS & HARDWARE REQUIRED FOR A COMPLETE SYSTEM.
4. EMERGENCY BATTERY DRIVER WHEN INDICATED IN LED FIXTURES, SHALL PROVIDE A MINIMUM OF 1300 LUMEN OUTPUT. DRIVER SHALL CONTAIN INTEGRAL SENSING CIRCUIT TO ALLOW FIXTURE TO BE SWITCHED WITH AREA FIXTURES FOR NORMAL OPERATION WHERE INDICATED, AND ENERGIZED EQUALLY UPON LOSS OF POWER CIRCUIT, REGARDLESS OF SWITCH POSITION.
5. CONTRACTOR TO COORDINATE AND DETERMINE EXACT MOUNTING HEIGHTS OF ALL INTERIOR AND EXTERIOR WALL MOUNTED LIGHT FIXTURES IN FIELD PRIOR TO ROUGH-IN. FIXTURES TO BE UNIFORM AND CONSISTENT IN ALL APPLICATIONS.

**LIGHTING FIXTURE SCHEDULE**

Fixture Type	Fixture Description	Acceptable Manufacturers	Lamps	Fixture Wattage	Voltage
EL	EXTERIOR WEATHERPROOF EMERGENCY EXTERIOR LED LIGHT FIXTURE WITH PE CELL.	EMERGILITE # LUX-ACDS-P	BY MANUFACTURER	12	MULTI
EL ALT.	EXTERIOR WEATHERPROOF EMERGENCY EXTERIOR LED LIGHT FIXTURE WITH PE CELL.	SLG LIGHTING # WCE-L13-G1-120/277V-PC-FSK-DB	BY MANUFACTURER	12	MULTI
EM	WALL MOUNTED SPECIFICATION GRADE TWIN-HEAD EMERGENCY LIGHT WITH BATTERY BACKUP, WHITE HOUSING.	EMERGILITE # EL-2LED	BY MANUFACTURER	11	MULTI
EM ALT.	WALL MOUNTED SPECIFICATION GRADE TWIN-HEAD EMERGENCY LIGHT WITH BATTERY BACKUP, WHITE HOUSING.	SLG LIGHTING # EL-TP-C1-120/277V-L-I-W	BY MANUFACTURER	11	MULTI
EXC	COMBINATION EMERGENCY LIGHT/EXIT SIGN WITH RED LED ON WHITE HOUSING, BATTERY BACKUP, DIFFUSER LENS, AND HIGH OUTPUT BATTERY BALLAST, SPEC. GRADE.	EMERGILITE # ELXN400R-2LEDR	BY MANUFACTURER	10	MULTI
EXC ALT.	COMBINATION EMERGENCY LIGHT/EXIT SIGN WITH RED LED ON WHITE HOUSING, BATTERY BACKUP, DIFFUSER LENS, AND HIGH OUTPUT BATTERY BALLAST, SPEC. GRADE.	COMPASS # CCRGRC	BY MANUFACTURER	10	MULTI
HL	HIGH BAY INDUSTRIAL LED FIXTURE WITH ALUMINUM REFLECTOR AND INTEGRAL OCCUPANCY SENSOR.	ORACLE # CB2-LED-18000L-DIM10-MVOLT-WD-40K-85	LED	180	MULTI
HL ALT.	HIGH BAY INDUSTRIAL LED FIXTURE VARIABLE LUMEN OUTPUT, AND INTEGRAL OCCUPANCY SENSOR.	COLUMBIA # CLH1-LSCS-EDU-WD	LED	180	MULTI
HLE	HIGH BAY INDUSTRIAL LED FIXTURE WITH ALUMINUM REFLECTOR, INTEGRAL OCCUPANCY SENSOR AND BATTERY BACK UP.	ORACLE # CB2-LED-18000L-DIM10-MVOLT-WD-40K-85-0-EMG-LED-20W	LED	180	MULTI
HLE ALT.	HIGH BAY INDUSTRIAL LED FIXTURE VARIABLE LUMEN OUTPUT, INTEGRAL OCCUPANCY SENSOR AND BATTERY BACK UP.	COLUMBIA # CLH1-LSCS-EDU-WD-ELL25	LED	180	MULTI
WP	IDA DARK-SKY APPROVED WALL-PAK, PRISMATIC GLASS REFLECTOR, DARK BRONZE HOUSING, U.L. WET LOCATION, 16' MAX. MOUNTING HEIGHT.	WILLIAMS # WWPV-L60-7-40	LED	70	MULTI
WP ALT.	IDA DARK-SKY APPROVED WALL-PAK, PRISMATIC GLASS REFLECTOR, DARK BRONZE HOUSING, U.L. WET LOCATION, 16' MAX. MOUNTING HEIGHT.	BEACON # VPW2-48L-4K7-XX-UNV-XX	LED	70	MULTI



**ELECTRICAL NOTES:**

1. FOR DRAWING CLARITY, INDIVIDUAL BRANCH CIRCUIT HOMERUNS ARE INDICATED. ELECTRICAL CONTRACTOR MAY RUN UP TO (3) 20A BRANCH CIRCUITS IN A SINGLE HOMERUN TO A COMMON PANEL.
2. PULL AN UNSWITCHED LEG OF THE LOCAL LIGHTING CIRCUIT TO ALL EXIT, EMERGENCY, AND NIGHT LIGHTING FIXTURES SHOWN UNLESS INDICATED OTHERWISE ON PLANS.
3. DETERMINE EXACT LOCATION FOR ALL LIGHT FIXTURES AND LIGHTING CONTROLS IN FIELD. COORDINATE WITH ARCHITECTURAL DRAWINGS AND ALL OTHER TRADES.


**CRAIG  
GAULDEN  
DAVIS**

• Architecture

19 Washington Park  
Greenville, SC 29601  
Phone 864.242.0761  
Fax 864.501.9945  
E-mail cgd@cgdarch.com

COPYRIGHT © 2025 CRAIG GAULDEN DAVIS | PBK  
ALL RIGHTS RESERVED

THIS COPYRIGHTED DOCUMENT AND ALL  
INFORMATION CONTAINED HEREIN IS AN  
INSTRUMENT OF SERVICE AND SHALL NOT BE  
REPRODUCED, ALTERED, OR REUSED IN PART  
OR IN WHOLE WITHOUT PRIOR WRITTEN  
PERMISSION FROM THE ARCHITECT. THIS  
DRAWING IS THE EXCLUSIVE PROPERTY OF  
THE ARCHITECT AND MUST BE RETURNED  
UPON REQUEST.



CONSULTANT

**ICES**  
Carolina ENGINEERING SOLUTIONS, LLC  
8 WEST MCGEE AVE, Suite 203  
Greenville, SOUTH CAROLINA 29601  
pH: (864) 370-9395 FAX: (864) 370-9505  
WWW.CarolinaENGR.COM

PROJECT

A NEW STORAGE BUILDING


**PIEDMONT  
TECHNICAL  
COLLEGE**

GREENWOOD, SC

ISSUE: BID DOCUMENTS  
DATE: 11/25/25  
PROJECT NO: 25-125  
DRAWN BY: RBP  
CHECKED BY: JDJ

**ELECTRICAL  
LIGHTING PLAN**

**E1.1**



1  
E2.1 1/4" = 1'-0"

ELECTRICAL POWER PLAN

MECHANICAL EQUIPMENT ELECTRICAL SCHEDULE				
EQUIP.	CIRCUIT #	FEEDER	LOCAL DISCONNECT/STARTER	NOTES
WEF-1	RP-7/9	2#10, #12G-3/4"	30/2 F/F/3R/SIZE 1	1,2,3
LV-1	RP-11	2#12, #12G-3/4"	TOGGLE TYPE	1,2,3
LV-2	RP-11	2#12, #12G-3/4"	TOGGLE TYPE	1,2,3

NOTES:

1. CONTRACTOR TO COORDINATE WITH MECHANICAL DRAWINGS FOR EXACT LOCATION OF ALL MECHANICAL EQUIPMENT. LOCATION OF MECHANICAL EQUIPMENT SHOWN ARE FOR GENERAL INFORMATION PURPOSES ONLY.
2. INSTALL DISCONNECTING MEANS ADJACENT AND ACCESSIBLE TO ALL MECHANICAL EQUIPMENT. FIELD COORDINATE EXACT MOUNTING LOCATION.
3. PROVIDE ALL NECESSARY INTERCONNECTION WIRING BETWEEN EF & MOTORIZED LOUVER.

POWER NOTES:

1. FOR DRAWING CLARITY, INDIVIDUAL BRANCH CIRCUIT HOMERUNS ARE INDICATED. ELECTRICAL CONTRACTOR MAY RUN UP TO (3) 20A BRANCH CIRCUITS IN A SINGLE HOMERUN TO A COMMON PANEL.
2. VERIFY ALL LOCATIONS, ELECTRICAL CIRCUIT AND CONNECTION REQUIREMENTS FOR ALL HVAC AND PLUMBING EQUIPMENT WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN. SEE "MECHANICAL EQUIPMENT ELECTRICAL SCHEDULE" FOR CIRCUIT AND WIRING REQUIREMENTS FOR ALL HVAC EQUIPMENT.
3. INTERLOCK MOTORIZED LOUVER TO OPERATE WITH EXHAUST FAN "WEF-1".


CRAIG  
GAULDEN  
DAVIS

● Architecture

19 Washington Park  
Greenville, SC 29601  
Phone 864.242.0761  
Fax 864.501.9945  
E-mail cgd@cgdarch.com

COPYRIGHT © 2025 CRAIG GAULDEN DAVIS | PBK  
ALL RIGHTS RESERVED

THIS COPYRIGHTED DOCUMENT AND ALL  
INFORMATION CONTAINED HEREIN IS AN  
INSTRUMENT OF SERVICE AND SHALL NOT BE  
REPRODUCED, ALTERED, OR REUSED IN PART  
OR IN WHOLE WITHOUT PRIOR WRITTEN  
PERMISSION FROM THE ARCHITECT. THIS  
DRAWING IS THE EXCLUSIVE PROPERTY OF  
THE ARCHITECT AND MUST BE RETURNED  
UPON REQUEST.



CONSULTANT

**ICES**  
Carolina ENGINEERING SOLUTIONS, LLC  
8 WEST MCGEE AVE, Suite 203  
Greenville, SOUTH CAROLINA 29601  
pH: (864) 370-9395 FAX: (864) 370-9505  
WWW.CarolinaENGR.COM

PROJECT

A NEW STORAGE BUILDING

PIEDMONT  
TECHNICAL  
COLLEGE

GREENWOOD, SC

ISSUE: BID DOCUMENTS  
DATE: 11/25/25  
PROJECT NO: 25-125  
DRAWN BY: RBP  
CHECKED BY: JDJ

ELECTRICAL  
POWER PLAN

E2.1